DERBIGUN[®] XPS-FR

Smooth surfaced, triple reinforced APP modified bitumen waterproofing membrane

ADVANTAGES

- High quality 4.0 mm (160 mils) smooth surfaced UL Class A fire-resistant APP modified bitumen roofing membrane
- Performance Roof Systems' exclusive blend of APP (atactic polypropylene) polymers and select asphalts enhances the weathering capabilities and UV resistance of the membrane
- Triple reinforced with a heat resistant non-woven fiberglass mat followed by a polyester scrim that increases the membrane's strength and durability
- Top placement of the reinforcement layers allow it to filter out harmful UV rays which reduces natural aging. Therefore the membrane does not require a granule surfacing or a roof coating for protection.
- ▶ Meets and exceeds requirements of ASTM D6223, Type II, Grade S
- Can be applied with PERMASTIC Cold Adhesive or heat welded

TECHNICAL CHARACTERISTICS



PROPERTY	MD	XMD	ASTM
Peak Load @ 0°F; lbf/in	255	285	D5147
Peak Load @ 73.4°F; lbf/in	140	165	D5147
Elongation at Peak Load @ 0°F; %	5	6	D5147
Elongation at Peak Load @ 73.4°F; %	5	5	D5147
Tear Resistance @ 73.4°F; lbf	270	325	D4073/D5147
Dimensional Stability; %	< 0.5	< 0.5	D1204/D5147
Low Temperature Flexibility @ 32°F	Pass	Pass	D5147
Compound Stability @ 230°F	Pass	Pass	D5147

PRODUCT INFORMATION*

PROPERTY	VALUE	
Thickness; mil (mm)	160 (4.0)	
Length; ft (m)	33.5 (10.2)	
Width; in (m)	39.4 (1.0)	
Weight; lb (kg)	98 (44.5)	
Net Coverage; ft ² (m ²)	100 (9.2)	

* All values shown are nominal and subject to normal manufacturing tolerances.

* All values shown are nominal and subject to normal manufacturing tolerances.

APPLICATION METHODS



PACKAGING & STORAGE

Packaged 20 rolls per pallet. Rolls should be stored on end, on raised platforms protected from the weather.



www.performanceroofsystems.us 4800 Dr. Martin Luther King Jr. Blvd., Kansas City, MO 64130 TOLL FREE: 800.727.9872 TEL: 816.921.0221

