OUTSIDE DIAMETER OF PENETRATION: ____ "

ENTER THE OUTSIDE DIAMETER MEASUREMENT

MINIMUM ____ "

MINIMUM 4"

MINIMUM 2"

MINIMUM 1" OVERLAP

REINFORCING FABRIC

MINIMUM ____ "

MINIMUM ____ "

MINIMUM 8"

MINIMUM

MINIMUM 8"   RAD. ____ "   DIA. ____ "   RAD. ____ "   MINIMUM 8"

REINFORCING FABRIC

MINIMUM 8"

MINIMUM 1" OVERLAP ON EACH TARGET TOTALLING A MINIMUM OF 2" OVERLAP

NOTES:
1. PERFORMANCE ROOF SYSTEMS DETAIL DRAWINGS: REFER TO PERFORMANCE ROOF SYSTEMS AND OTHER RELATED PUBLISHED DOCUMENTATION, PRODUCT DATA SHEETS (PDS) AND SAFETY DATA SHEETS (SDS) FOR ADDITIONAL INFORMATION. ALL DETAIL DRAWINGS AND RELATED INSTALLATION GUIDELINES ARE PROVIDED BY PERFORMANCE ROOF SYSTEMS FOR THE SOLE PURPOSE OF ISSUING A PERFORMANCE ROOF SYSTEMS WARRANTY. ACCORDINGLY, THE DETAIL DRAWINGS ARE NOT OFFERED, AND SHOULD NOT BE CONSIDERED, AS A SUBSTITUTE FOR PROFESSIONAL DESIGN SERVICES.

PERFORMANCE ROOF SYSTEMS
A SOPREMA GROUP COMPANY

4800 DR. MARTIN LUTHER KING JR. BLVD.
KANSAS CITY, MO 64130
www.performanceroofsystems.us
Tel:816.921.0221

PROJECT:

DRAWN BY: PRS TECHNICAL SUPPORT, GGALLOWAY

NO.:		REVISION:	DATE:

TITLE:
LIQUID FLASHING, ROUND PENETRATION FLEECE CUTTING PATTERN

DATE: 07.15.2022

SCALE: NTS

DRAWING NUMBER:
US.PRS.RM2APP.02.01