


STEEP SLOPE MEMBRANE FASTENING REQUIREMENTS							
METHOD OF APPLICATION		CAP SHEET END LAP MAXIMUM SPAN ("X")					
BASE PLY(S)	CAP SHEET	1/2:12 to 1:12	1:12 to 2:12	2:12 to 3:12	3:12 to 6:12	6:12 to 12:12	GREATER THAN 12:12
HEAT WELDED	COLD ADHERED	32'	24'	16'	16'	12'	NR
	HEAT WELDED	n/a	n/a	24'	16'	12'	4'
COLD ADHERED	HEAT WELDED	32'	24'	16'	16'	12'	NR
	COLD ADHERED	32'	24'	16'	16'	12'	NR

n/a = Cap sheet end lap spans are not limited. End lap fastening is not required.

NR = Assembly is not recommended at specified slope.

**NOTES:**

1. PERFORMANCE ROOF SYSTEMS DETAIL DRAWINGS: REFER TO PERFORMANCE ROOF SYSTEMS AND OTHER RELATED PUBLISHED DOCUMENTATION, PRODUCT DATA SHEETS (PDS) AND SAFETY DATA SHEETS (SDS) FOR ADDITIONAL INFORMATION. ALL DETAIL DRAWINGS AND RELATED INSTALLATION GUIDELINES ARE PROVIDED BY PERFORMANCE ROOF SYSTEMS FOR THE SOLE PURPOSE OF ISSUING A PERFORMANCE ROOF SYSTEMS WARRANTY. ACCORDINGLY, THE DETAIL DRAWINGS ARE NOT OFFERED, AND SHOULD NOT BE CONSIDERED, AS A SUBSTITUTE FOR PROFESSIONAL DESIGN SERVICES.
2. HOT WORK: THE CONTRACTOR IS RESPONSIBLE FOR DETERMINING APPROPRIATE CONDITIONS TO UTILIZE HEAT-WELDING EQUIPMENT. REFER TO THE NRCA CERTA RECOMMENDATIONS, LOCAL CODES AND BUILDING OWNER'S REQUIREMENTS FOR HOT WORK OPERATIONS.
3. PRIMER: WHERE NOT SHOWN OR INDICATED ON DETAIL DRAWINGS, REFER TO MATERIAL PRODUCT DATA SHEETS FOR PRIMER APPLICATION REQUIREMENTS.

 <p>4800 DR. MARTIN LUTHER KING JR. BLVD. KANSAS CITY, MO 64130 www.performancerooftsystems.us Tel: 816.921.0221</p>	PROJECT:	DRAWN BY: PRS TECHNICAL SUPPORT, GGALLOWAY		
	TITLE:	NO.:	REVISION:	DATE:
	<b>APP MEMBRANE STEEP SLOPE FASTENING</b>	DATE: 07.22.2022	DRAWING NUMBER: <b>US.PRS.RM2APP.02.10</b>	
		SCALE: NTS		