

# DUOTACK<sup>®</sup> 365 ADHESIVE



## MATERIALS & RESOURCES



### Recycled Content (MRc3)

DUOTACK 365 Adhesive is manufactured using recycled material. The percentage of recycled material is calculated by individual weight. Recycled content = (post-consumer + 1/2 pre-consumer)

RECYCLED CONTENT	POST-CONSUMER WEIGHT	PRE-CONSUMER WEIGHT
1.9 %	0 %	3.8 %

### Regional Materials (MRc3)

If the project is within 100 miles of the manufacturing site, LEED credit may apply.

MANUFACTURER	LOCATION
SOPREMA Canada	Drummondville, Quebec

## ENVIRONMENTAL QUALITY



### Low-Emitting Materials (EQc2)

Reduce the number of indoor air contaminants that are odorous, irritating and/or harmful to the comfort and wellbeing of installers and occupants. Performance Roof Systems certifies volatile organic content (VOC) levels for the products listed above. Products with VOC limits established in South Coast Air Quality Management District (SCAQMD) Rule 1113 for Traffic Coatings (< 100 g/L) may be considered for this credit.

VOC
0 g/L

*DISCLAIMER: All LEED rating point references are based on suggested applications of Performance Roof Systems products. LEED applicants should use their own objective determinations of product attributes for certification purposes.*