

DERBIBASE SA ULTRA

Polyester reinforced SBS modified bitumen self adhered base sheet

ADVANTAGES

- ▶ High quality SBS (Styrene-Butadiene-Styrene) rubber and asphalt blend that lends elasticity and flexibility to the sheet
- ▶ Constructed with high performance polyester reinforcement providing exceptional tensile strength and dimensional stability
- ▶ Mineral surfacing provides for exceptional bonding to heat welded inter-ply or cap sheets
- ▶ Split-film release allows for easy removal and quicker installation
- ▶ Specially formulated high-tack adhesive forms an immediate long-lasting bond
- ▶ Self-adhered application allows for quick and easy installation



TECHNICAL CHARACTERISTICS

DERBIBASE SA ULTRA Results*

PROPERTY	MD	XMD	ASTM
Peak Load @ 0°F; lbf/in	110	85	D5147
Peak Load @ 73.4°F; lbf/in	85	65	D5147
Elongation at Peak Load @ 0°F; %	35	40	D5147
Elongation at Peak Load @ 73.4°F; %	55	60	D5147
Ultimate Elongation @ 73.4°F; %	60	65	D5147
Tear Resistance @ 73.4°F; lbf	125	85	D5147
Dimensional Stability; %	< 0.5	< 0.5	D5147
Low Temperature Flexibility @ 32°F	Pass	Pass	D5147
Compound Stability @ 230°F	Pass	Pass	D5147

* All values shown are nominal and subject to normal manufacturing tolerances.

PRODUCT INFORMATION*

PROPERTY	VALUE
Thickness; mil (mm)	106 (2.7)
Length; ft (m)	49.2 (15.0)
Width; in (m)	39.4 (1.0)
Weight; lb (kg)	103 (46.5)
Net Coverage; ft ² (m ²)	147.6 (13.7)

* All values shown are nominal and subject to normal manufacturing tolerances.

PACKAGING & STORAGE

Packaged 20 rolls per pallet. Store rolls on end and maintain in an upright position to prevent damage. Store rolls in a clean, dry location and cover as necessary to protect rolls from environmental damage such as extreme cold, heat, or moisture.



www.performancerooftsystems.us
4800 Dr. Martin Luther King Jr. Blvd., Kansas City, MO 64130
TOLL FREE: 800.727.9872 TEL: 816.921.0221



Florida State
Wide Approval



MIAMI-DADE COUNTY
APPROVED

REV. 05.23