


DERBICOLOR[®]P

Granule surfaced, polyester reinforced APP modified bitumen waterproofing membrane

ADVANTAGES

- ▶ High quality 4.1 mm (161 mils) granule surfaced APP modified bitumen roofing membrane
- ▶ Performance Roof Systems' exclusive blend of APP (atactic polypropylene) polymers and select asphalts enhances the weathering capabilities and UV resistance of the membrane
- ▶ Reinforced with a heat resistant a 180 gram polyester mat that increases the membrane's strength and durability
- ▶ Mineral surfacing provides added resistance to weathering and foot traffic
- ▶ Meets and exceeds requirements of ASTM D6222, Type I, Grade G
- ▶ Can be applied with PERMASTIC Cold Adhesive or heat welded



TECHNICAL CHARACTERISTICS

DERBICOLOR[®]P Results*

PROPERTY	MD	XMD	ASTM
Peak Load @ 0°F; lbf/in	90	65	D5147
Peak Load @ 73.4°F; lbf/in	80	60	D5147
Elongation at Peak Load @ 0°F; %	35	35	D5147
Elongation at Peak Load @ 73.4°F; %	55	60	D5147
Ultimate Elongation @ 73.4°F; %	58	67	D5147
Tear Resistance @ 73.4°F; lbf	100	80	D5147
Dimensional Stability; %	0.5	0.4	D1204/D5147
Low Temperature Flexibility @ 32°F	Pass	Pass	D5147

PROPERTY	MINIMUM	ASTM
Compound Stability @ 230°F	Pass	D5147
Granule Embedment; g	< 2.0	D4977/D5147

* All values shown are nominal and subject to normal manufacturing tolerances.

PRODUCT INFORMATION*

PROPERTY	VALUE
Thickness; mil (mm)	161 (4.1)
Length; ft (m)	33.5 (10.2)
Width; in (m)	39.4 (1.0)
Weight; lb (kg)	101 (45.8)
Net Coverage; ft ² (m ²)	100 (9.2)

* All values shown are nominal and subject to normal manufacturing tolerances.

AVAILABLE COLORS



**CUSTOM
COLOR OPTIONS
AVAILABLE**

PACKAGING & STORAGE

Packaged 20 rolls per pallet. Rolls should be stored on end, on raised platforms protected from the weather.



**PERFORMANCE
ROOF SYSTEMS**
A SOPREMA GROUP COMPANY

www.performancerooftsystems.us
4800 Dr. Martin Luther King Jr. Blvd., Kansas City, MO 64130
TOLL FREE: 800.727.9872 TEL: 816.921.0221



Florida State
Wide Approval



MIAMI-DADE COUNTY
APPROVED

REV. 03.23