DERBIFLASH RS COLOR ADDITIVE

DESCRIPTION

Derbiflash RS Color Additives are high-quality, concentrated pigments designed to be mixed with Derbiflash RS 287 Color Base resin to create custom finishes for Derbiflash RS systems.

ADVANTAGES

- ▶ Pre-measured for easy application
- ► Available in 14 colors
- Non-toxic, Low odor
- ► Readily mixes into RS resins

MIXING INSTRUCTIONS

One pouch of Derbiflash RS Color Additive is required for each 8.5 kg container of Derbiflash RS 287 Color Finish Base.

Derbiflash RS Color Additive should be thoroughly mixed prior to being added to the liquid resin. Using a slow-speed (200-400 rpm) mechanical agitator, mix the color additive for 2 - 5 minutes until uniform streak-free color is achieved. Next, add the entire contents of Derbiflash RS Color Additive to the liquid resin and continue mixing for 2 - 5 minutes. **NOTE:** Combining the color additive to Derbiflash RS 287 Color Base does not affect shelf-life or storage.

Refer to Derbiflash RS 287 Color Base product data sheets for additional information regarding mixing, application and use.

AVAILABLE COLORS

COLOR	PRODUCT#
Signal White	AC-101
Light Grey	AC-102
Pebble Grey	AC-103
Window Grey	AC-104
Stone Grey	AC-105
Beige	AC-106
Terra Cotta	AC-107
Traffic Yellow	AC-108
Pale Green	AC-109
Traffic Green	AC-110
Traffic Blue	AC-111
Traffic Red	AC-112
Traffic Black	AC-113
Traffic Grey	AC-114

LIMITATIONS

Derbiflash RS Color Additive is specifically designed for use with Derbiflash RS 287 Color Base.

STORAGE & HANDLING

Containers should be stored in a cool, dry indoor environment at temperatures between 32 - 77°F. PROTECT FROM FREEZING. Approximate shelf life is 12 months from date of shipment when properly stored, sealed and unmixed.

CLEAN UP

For wet material use soap and water; For cured material use mineral spirits or citrus-based cleaners

