

DERBIFLASH RS LIQUID THIXO

DESCRIPTION

Derbiflash RS Liquid Thixo is a proprietary thixotropic additive for Derbiflash RS resins and top coats. Derbiflash RS Liquid Thixo increases resin viscosity to reduce slumping and run-off for steep slope and vertical applications.

APPROVED FOR USE WITH

- Derbiflash RS 230 Flash
- Derbiflash RS 230 Field
- Derbiflash RS 210 Mortar Base
- Derbiflash RS 287 Colored Base
- Derbiflash RS 289 Textured Base
- Derbiflash RS Textured Coating

MIXING INSTRUCTIONS

For vertical substrates or slopes exceeding 1 1/2 : 12, pre-mix the Derbiflash RS resin with Derbiflash RS Liquid Thixo at up to 2% addition by weight. Derbiflash RS Liquid Thixo can be measured using a standard tablespoon, where 1 TBSP equals approximately 20 g (0.02 kg). **NOTE:** Storage and working times of Derbiflash RS resins are not affected by addition of Derbiflash RS Liquid Thixo.

Prior to use or application, refer to product data sheets and labels for complete application instructions for the specific Derbiflash RS resin being used.

TECHNICAL CHARACTERISTICS *

PROPERTY	VALUE
Color	Transparent
Size	1 KG
Weight	3.3 lb
VOC content	< 20 g/L

* All values shown are nominal and subject to normal manufacturing tolerances.

LIMITATIONS

Performance Roof Systems recommends testing the amount of Derbiflash RS Liquid Thixo required by mixing small batches before mixing entire units of product. Resin mixed with Derbiflash RS Liquid Thixo must be allowed to stand 20 - 30 minutes before use.

CLEAN UP

Brushes and rollers will remain pliable and usable if they are kept moving in liquid resin. If allowed to sit, they will stiffen quickly as resin begins to cure. Rollers and brushes should be discarded once they harden. Roller handles and metal tools may be cleaned with Derbiflash RS Cleaner. To minimize cleaning, wipe reusable handles and tools with clean, dry cloth as needed before resin components cure.

STORAGE & HANDLING

Containers should be stored in a cool, dry indoor environment at temperatures between 32 - 77°F. PROTECT FROM FREEZING. Approximate shelf life is 12 months from date of shipment when properly stored, sealed and unmixed.