Fiberglass reinforced, SBS modified bitumen aluminum surfaced waterproofing membrane

DESCRIPTION

Derbilume FR is an SBS-modified bitumen caps sheet for use in approved multi-ply membrane and flashing assemblies. Derbilume FR is composed of a proprietary formulation of elastomeric styrenebutadiene-styrene (SBS) polymer modified bitumen and is reinforced with a high strength glass scrim. The topside is surfaced with an aluminum foil and underside is surfaced with polyolefin burn-off film to optimize heat welding.

APPLICATION

Prior to installation, unroll Derbilume FR onto the roof surface and allow to relax. Once positioned, back roll the product and install using standard heat welding practices. For complete application instructions contact Performance Roof Systems Technical Services for recommendations.

TECHNICAL CHARACTERISTICS

ADVANTAGES

- High-quality, SBS rubber and asphalt blends provides excellent cold temperature flexibility and elongation properties
- Fiberglass reinforcement adds excellent dimensional stability and tensile strength to the membrane
- Polyolefin burn-off film helps optimize heat welding application
- Embossed aluminum surfacing pleasing aesthetics and reflectivity that can add beneficial energy-savings
- For Flashing details the aluminum surfacing offers an ideal substrate for adhesion

DERBILUME[®] FR Results*

| PROPERTY | MD | XMD | ASTM | |
|-------------------------------------|-------|-------|-------------|--|
| Peak Load @ 0°F; lbf/in | 200 | 175 | D6298 | |
| Peak Load @ 73.4°F; lbf/in | 95 | 95 | D6298 | |
| Elongation at Peak Load @ 0°F; % | 10 | 10 | D6298 | |
| Elongation at Peak Load @ 73.4°F; % | 20 | 20 | D6298 | |
| Tear Resistance @ 73.4°F; lbf | 190 | 205 | D6298 | |
| Dimensional Stability; % | < 0.2 | < 0.2 | D1204/D5147 | |
| Low Temperature Flexibility@ 32°F | Pass | Pass | D1876 | |
| Compound Stability @ 230°F | Pass | Pass | D5147 | |

* All values shown are nominal and subject to normal manufacturing tolerances.

PRODUCT INFORMATION*

| PROPERTY | VALUE |
|---|--------------------|
| Thickness; mil (mm) | 157 (4.0) |
| Length; ft (m) | 32.8 (10.0) |
| Width; in (m) | 39.4 (1.0) |
| Weight; lb (kg) | 94 (42.7) |
| Net Coverage; ft ² (m ²) | 96.6 (9.0) |

* All values shown are nominal and subject to normal manufacturing tolerances.

PACKAGING & STORAGE

Packaged 25 rolls per pallet. Rolls should be stored on end, on raised platforms protected from the weather.

ENERGY & ENVIRONMENT

| PROPERTY | ASTM | INITIAL | 3-YEAR* |
|-------------------------|-------|---------|---------|
| Solar Reflectance | C1549 | 0.87 | 0.72 |
| Thermal Emittance | E1371 | 0.05 | 0.10 |
| Solar Reflectance Index | E1980 | 93 | 64 |

* 3-year values shown are the CRRC Rapid Ratings values.





www.performanceroofsystems.us 4800 Dr. Martin Luther King Jr. Blvd., Kansas City, MO 64130 TOLL FREE: 800.727.9872 TEL: 816.921.0221