

PRS GLASS BASE

Fiberglass base sheet

ADVANTAGES

- ▶ High quality base or ply sheet constructed from fiberglass mat coated with oxidized asphalt
- ▶ Product is intended to be used over lightweight insulating fill decks, gypsum or other substrates where lateral venting is required.
- ▶ Meets or exceeds ASTM D4601 Type II specifications
- ▶ Adds inter-ply adhesion between base ply and the membrane
- ▶ Made from inorganic material that resists rotting
- ▶ Manufactured with ply lines for easy installation
- ▶ Can be applied using hot asphalt or mechanical fasteners

TECHNICAL CHARACTERISTICS

PRS Glass Base Results*

PROPERTY	MD	XMD	ASTM
Peak Load @ 73.4°F; lbf/in	63	63	D4601

* All values shown are nominal and subject to normal manufacturing tolerances.

PRODUCT INFORMATION*

PROPERTY	VALUE
Length; ft (m)	108 (32.9)
Width; in (m)	36 (0.9)
Weight; lb (kg)	78.5 (36.5)
Net Coverage; ft ² (m ²)**	291.7 (27)

* All values shown are nominal and subject to normal manufacturing tolerances
 **Net coverage is configured to reflect overlaps according to Performance Roof Systems specifications.
 Coverage rates can vary depending on project specifications.

PACKAGING & STORAGE

Packaged 20 rolls per pallet. Rolls should be stored on end, on raised platforms protected from the weather.

