

PERLOK METAL SEAM PLATES

DESCRIPTION

PERLOK METAL SEAM PLATES are used to mechanically attach single-ply and modified bituminous roof membranes to the substrate. The plates circular design and reinforcing ribs provide exceptional strength and uplift resistance.

PRODUCT SELECTION

PERLOK 2" Metal Seam Plates are used within fully bonded seams to attach reinforced and non-reinforced base sheets. Approved for use with PERLOK #14HD, #14SSHD, #15EHD, Fluted Concrete Nail and 1/4" Concrete Spike fasteners.

PERLOK 2" & 2.4" Barbed Metal Seam Plates attach reinforced single-ply and modified bituminous membranes. Approved for use with PERLOK #14HD, #14SSHD, #15EHD, Purlin, Fluted Concrete Nail or 1/4" Concrete Spike fasteners.

PRODUCT SPECIFICATIONS

PRODUCT	PART #	PKG QTY	PKG WEIGHT	PALLET QTY
PERLOK 2" Metal Seam Plate	MP-2000	1,000/Bucket	27 lb	60,000
PERLOK 2" Barbed Metal Seam Plate	MPB-2000	1,000/Bucket	28 lb	40,000
PERLOK 2.4" Barbed Metal Seam Plate	MPB-2400	1,000/Bucket	52 lb	24,000

TYPICAL PROPERTIES*

PROPERTY	VALUE
Material	26 Gauge Steel
Coating	Galvalume AZ-55
Corrosion Resistance	<15% Red rust after 30 cycles
Recycled content	49%

