

PERLOK TL METAL PLATES

DESCRIPTION

PERLOK TL METAL PLATES circular design and reinforcing ribs provide exceptional strength and uplift resistance. PERLOK TL METAL PLATES are made of Galvalume coated steel for excellent corrosion protection that meet the requirements of ASTM D6294, FM 4470 and DIN 50018.

PRODUCT SELECTION

PERLOK 3" TL Insulation Plate is used to attach roof insulation, coverboards and BUR base sheets to cementitious wood fiber, gypsum and lightweight concrete substrates.


PERLOK 2" TL Seam Plate are used to attach reinforced single-ply and modified bituminous membranes to cementitious wood fiber, gypsum and lightweight concrete substrates.

PRODUCT SPECIFICATIONS

PRODUCT	PART #	PKG QTY	PKG WEIGHT	PALLET QTY
PERLOK 3" TL Insulation Plate	MPTL-3000	500/Bucket	17.5 lb	36,000
PERLOK 2" TL Seam Plate	MPTL-2000	1,000/Carton	14 lb	48,000

TYPICAL PROPERTIES *

PROPERTY	VALUE
Material	26 Gauge Steel
Coating	Galvalume AZ-55
Hole Diameter	0.625"
Corrosion Resistance	<15% Red rust after 30 cycles
Recycled content	49%



PERLOK 3" TL Insulation Plate



PERLOK 2" TL Seam Plate