

# SEAM PLATES

## DESCRIPTION

Metal Seam Plates are used to mechanically attach single-ply and modified bituminous roof membranes to the substrate. The plates circular design and reinforcing ribs provide exceptional strength and uplift resistance.

## PRODUCT SELECTION

**2" Metal Seam Plate** is used within fully bonded seams to attach reinforced and non-reinforced base sheets. Approved for use with #14HD, #14SSHD, #15EHD, Fluted Concrete Nail and 1/4" Concrete Spike fasteners.

**2" & 2.4" Barbed Metal Seam Plate** are used to attach reinforced single-ply and modified bituminous membranes. Approved for use with #14HD, #14SSHD, #15EHD, Purlin, Fluted Concrete Nail or 1/4" Concrete Spike fasteners.

## PRODUCT SPECIFICATIONS

| PRODUCT                      | PART #   | PKG QTY      | PKG WEIGHT | PALLET QTY |
|------------------------------|----------|--------------|------------|------------|
| 2" Metal Seam Plate          | MP-2000  | 1,000/Bucket | 27 lb      | 60,000     |
| 2" Barbed Metal Seam Plate   | MPB-2000 | 1,000/Bucket | 28 lb      | 40,000     |
| 2.4" Barbed Metal Seam Plate | MPB-2400 | 1,000/Bucket | 52 lb      | 24,000     |

## TYPICAL PROPERTIES\*

| PROPERTY                    | VALUE                         |
|-----------------------------|-------------------------------|
| <b>Material</b>             | 26 Gauge Steel                |
| <b>Coating</b>              | Galvalume AZ-55               |
| <b>Corrosion Resistance</b> | <15% Red rust after 30 cycles |
| <b>Recycled content</b>     | 49%                           |

