

# SENTINEL® PVC BOOT FLASHING

Boot Flashing utilizing fiberglass reinforced PVC Membrane

## DESCRIPTION

The SENTINEL® PVC Boot Flashing is a factory fabricated pipe flashing utilizing fiberglass reinforced pvc membrane. The SENTINEL® PVC Boot Flashing is available in two sizes and fits either a 1" - 6" pipe or a 6" - 12" pipe. The 'closed' style flashing is used for penetrations where the flashing can be slipped over the top of the penetration and moved down into position. The split style flashings are great where the pipe is not accessible due to equipment or other obstruction at the top of the pipe and require field welding of the vertical seam. Each pipe flashing is shipped with a stainless steel clamping ring.

## PRODUCT INFORMATION

PRODUCT # / COLOR	FITS PIPE DIAMETER (inches)	STYLE	QTY/BOX
<b>P610</b> (White)	1 - 6	Split	10
<b>P610-T</b> (Tan)			
<b>P610-T</b> (Grey)			
<b>P611</b> (White)	1 - 6	Closed	10
<b>P611-T</b> (Tan)			
<b>P611-T</b> (Grey)			
<b>P612</b> (White)	6 - 12	Split	10
<b>P612-T</b> (Tan)			
<b>P612-T</b> (Grey)			
<b>P613</b> (White)	6 - 12	Closed	10
<b>P613-T</b> (Tan)			
<b>P613-T</b> (Grey)			



## APPLICATION

SENTINEL® PVC Boot Flashings are hot-air welded to the field membrane. Seal the top of the pipe flashing watertight with mastic and a pipe clamp (included). Refer to Performance Roof Systems specifications and installation instructions for additional application guidelines.

## STORAGE & HANDLING

All materials must be stored in a clean, dry location and cover as necessary to protect from environmental damage such as extreme cold, heat or moisture. Monitor varying environmental conditions during storage, handling and application.