FIELD 7" O.C. IN THE SIDE LAPS AND 2 STAGGERED, EQUALLY SPACED ROWS 7" O.C

CORNER
4.5" O.C. IN THE
SIDE LAPS AND 4
STAGGERED,
EQUALLY SPACED
ROWS 4.5" O.C

4.5" 💿 4.5" (0) \odot 1 (0) 4.5" (0) (0) (0) (0) (0) (e) \odot L (0) \odot 1 5.5" ① $\odot_{\mathbf{1}}$ 7" **⊙** (0) (0) 5.5" **O O** 7" 5.5" **⊙** (0) <u></u> <u></u> ⊚ **⊙** (0) (0) (0) (0) (e) (0) (0) (0) (0) (0) (0) (0) (0) (O) (0) PERIMETER WIDTH →

(0)

(O)-

.5"⊚

PERIMETER
5.5" O.C. IN THE
SIDE LAPS AND 3
STAGGERED,
EQUALLY SPACED
ROWS 5.5" O.C

NOTES:

- 1. FASTENING PATTERNS ARE BASED OFF FM GLOBAL DATA SHEET 1-29. SEE FM 1-29 FOR RESTRICTIONS.
- 2. CORNER AND PERIMETER DIMENSIONS ARE BUILDING SPECIFIC. CALCULATED CORNER AND PERIMETER DIMENSIONS IN ACCORDANCE WITH FM GLOBAL DATA SHEET 1-28.
- 3. FOR USE ON LIGHTWEIGHT CONCRETE, GYPSUM, OR TECTUM.

DERBIGUM®
MAKING BUILDINGS SMART

F-1 NAILABLE DECK FASTENING PATTERN

03/15/16

DRW CHK REV
JS -- 0

ISSUED

F-1 SD

DERBIGUM AMERICAS, INC. | WWW.DERBIGUM.US