

PERMASTIC

Asphaltic-based cold-applied adhesive for modified bitumen membranes

ADVANTAGES

- ▶ Cold applied adhesive for use with modified bitumen membranes, base sheets, and other cold process roofing systems.
- ▶ Excellent adhesion and enhanced waterproofing due to over 80% solids content.
- ▶ Thixotropic properties from additives improve stability.
- ▶ Improved productivity which minimizes open roofs.
- ▶ Available in environmentally friendly reusable pails, drums and tanks
- ▶ No kettles, dangerous chemicals and low VOC emissions provides a safer work environment.
- ▶ Meets the requirements of ASTM D3019, Type III, Grade 2

PRODUCT INFORMATION*

PROPERTY	VALUE
Weight; lb/gal (kg/L)	9.0 (1.07)
VOC; lb/gal (g/L)	1.6 (200)
Flash point; °F (°C)	> 105 (>40.5)
Non-volatile contents	78 - 83% solids

* All values shown are nominal and subject to normal manufacturing tolerances.

APPLICATION

RATE: 2.0 gallons per 100 sq ft (90.81 sq m)

TOOLS: A notched squeegee or spray apparatus to distribute cold process adhesives.
A 20 lb steel roller to roll all side and ends laps that will be heat welded.

PACKAGING & STORAGE

PERMASTIC is available in the following containers sizes:

- 5 gallon pail (18.9 L) (4.7 gal per volume)
- 55 gallon drum (208.2 L) (53.3 gal per volume)
- 350 gallon reusable tank (1,323 L)

Store in a well-ventilated area far away from any heat source.

